MANUAL SPRAY GUNS

www.airgunsa.com

AZ 3 HTE
Gravity Spray Gun

- Light and Handy
- High Transfer Efficiency
- Extremely Fine Atomization, tested by the major Paint Producers

CERTIFICATE OF COMPLIANCE

We certify that we have tested the Air Gunsa AZ3 HTE Gravity Spray Gun in accordance with prEN 13966-1 Method 2 - Tests for transfer efficiency and that this spray gun complies with the requirements of the Environmental Protection Act 1990, Part I - 1997 Revision as detailed in PG6/34(97), PG6/23(97), PG6/40(94), PG6/41(94).

Transfer efficiencies achieved with the materials detailed in the test report were:

PRIMER	93.8%
SOLID COLOUR	78.4%
BASECOAT	81.5%
CLEAR LACQUER	77.9%

Signed for MIRRC THATCHAM: M. Smith, Chief Executive

THATCHAM
THE MOTOR INSURANCE REPAIR RESEARCH CENTRE
Colthrop Way, Thatcham, Berkshire, RG19 4NR U.K.

Model	Ø mm	bar	Nℓ/min	mℓ/min	mm	No.	g
AZ3 HTE AZ3 HTE AV	1.0	2.0	200	80	170	*5110	680
	1.3			150	240	*5113	
	1.5			190	260	*5115	
	1.8		205	260	300	*5118	
	2.0		205	265	310	*5120	
	2.5	3.0	279	424	340	*1400	710
	2.8		291	427	350	*3300	
	3.0		288	489	360	*1500	
	3.5		307	490	340	*1600	

Max. Working Pressure: 6.8 bar (98 PSI) Noise Level (LAeqT) 77.6 dB (A)

Temperature range: 5~40° C Air nipple: G 1/4" Fluid nipple: G 1/4"

CE Ex II 2 G X
declaration of ATEX conformity for use in zone 1 and in zone 2

ANEST IWATA

ANEST IWATA U.K. Ltd.
Unit 10 Little End Road,Eaton Socon,
St. Neots - Cambridgeshire - PE19 8JH
Tel. +44 (0) 1480 405419
Fax: +44 (0) 1480 217610
enquiries@anest-iwata.co.uk
www.anest-iwata.co.uk

Distributed by: